





- 1. Review storm impacts for 3, 5, and 10 year surrogate storms
- 2. Review selection of Hurricane Ida as our surrogate storm
- 3. Show the Problems
- 4. Define the 537 Plan Objectives
- 5. Review Overall Approach for Fixing Problems
- 6. Explain how we model I&I Reductions
- Next steps



Summary of Key Flows

	Storm	Return Frequency	Event Rainfall (inches)	2021 Total SSO Volume (MG)	2050 Total SSO Volume (MG)*	2021 SSO Duration (days)	2050 SSO Duration (days)		2050 Number of Overflow Locations*	2021 Peak Flow to KI (MGD)		2021 Bypass Volume (MG)	2050 Bypass Volume (MG)
	Isaias	10-Year	5.0	35	59	1.1		94	136	212	256	4.0	5.6
	Ivan	5-Year	4.3	31	52	1.0		60	83	175	212	3.7	5.2
l	Violet	5-Year	3.5	20	39	1.0		53	86	169	209	3.1	4.0
	Ida	5-Year	4.2	21	38	1.0		47	79	<mark>166</mark>	<mark>202</mark>	2.6	3.8
İ	Iris	3-Year	3.7	11	33	1.1		31	54	132	164	2.6	3.6
	Kyle	3-Year	3.8	18	32	0.8		47	72	158	190	2.5	4.0

Top SSO Manholes




	Isaias SSO		Isaias SSO Ivan SSO Volume		Viole	Violet SSO			Iris SSO Volume		Kyle SSO	
Тор	Volume (MG)		(MG)		Volume (MG)		Ida SSO Volume (MG)		(MG)		Volume (MG)	
Manholes	2021	2050	2021	2050	2021	2050	2021	2050	2021	2050	2021	2050
X8	5.27	7.12	5.47	6.85	3.82	5.56	3.93	5.84	1.60	5.41	3.91	5.04
J_4_8	2.95	4.28	3.14	4.10	2.23	3.32	2.14	3.26	1.84	3.72	2.07	2.83
17_32C	2.71	4.11	2.95	3.59	2.34	3.17	2.41	3.41	1.27	3.61	2.01	2.57
U-58	0.54	4.84	0.44	4.07	0.13	4.63	0.25	2.86	0.15	4.01	0.31	2.17
199B	1.43	2.18	1.55	1.83	1.34	1.76	1.36	1.85	0.98	2.07	1.11	1.38
U_12_34	1.94	2.46	1.64	2.43	0.69	1.57	0.95	1.57	0.00	1.14	1.14	1.70
277E (D)	1.36	1.81	1.26	1.51	1.20	1.58	1.21	1.57	1.20	1.85	0.94	1.27
ATP001	0.00	2.06	0.00	2.35	0.00	2.79	0.00	1.69	0.00	2.51	0.00	0.87
R_1_2	1.63	2.40	1.08	1.88	0.44	0.87	0.69	1.27	0.03	0.24	0.36	0.85
C302K	0.94	1.22	0.93	1.39	0.58	0.88	0.56	0.92	0.09	0.30	0.23	0.51
X8A	0.97	1.26	0.82	1.23	0.30	0.57	0.48	0.76	0.06	0.40	0.52	0.86
4_27C	0.74	1.31	0.66	1.21	0.34	0.59	0.37	0.77	0.13	0.58	0.33	0.97
PLF174	0.84	1.07	0.78	0.98	0.39	0.54	0.52	0.70	0.13	0.27	0.54	0.75
25_1D	0.72	0.97	0.67	0.88	0.35	0.48	0.45	0.59	0.25	0.42	0.42	0.58
L-48	0.61	0.86	0.51	0.76	0.23	0.42	0.30	0.48	0.15	0.37	0.30	0.51
X_2_6	0.54	0.74	0.49	0.70	0.17	0.33	0.21	0.41	0.00	0.12	0.28	0.55
TCO	0.20	0.40	0.42	٥٢٢	0.27	0.27	0.70	A 2E	0.20	0.26	0.25	0.27




lda

Our 5-year design event

Ida 2021






Ida 2050

Volume lost

0.000 - 0.001

0.001 - 0.010 0.010 - 0.100 0.100 - 1.000 1.000 - 3.000 3.000 - 15.000



Northampton




537 Plan Objectives



- 1. Eliminate all the blossoms through 2035
- Sequence the work to build only when needed
- 3. Build non-modular infrastructure to 2050 flow conditions
- 4. Select the most life cycle costadvantageous solution
- Recognize long-term rehab needs for pipes and pumps and force mains
- 6. Minimize the number of independent Signatory projects constructed inside the City



Techniques for Fixing Problems





"What Makes Sense" I&I Reductions

A starting point for evaluating cost and benefit of I&I removal

Meter Name	Manhole ID	Signatory	Net LF of Pipe	Net Parcel Count	Gross Parcel Count
	20_11		64,042	1,707	1,707

Meter	
RDII Statistics Summary	
Dry Weather GPD/EDU	260
Average Dry Weather Flow, DWF (MGD)	0.443
Baseline Infiltration %	30%
Average Peaking Factor- Average Daily DWF	6.8
Average Peaking Factor- Actual Time of Day	6.5
Max Peaking Factor- Average Daily Flow	16.1
Max Peaking Factor- Actual Time of Day	13.3
Average RDII Flow Rate (MGD)	0.333
Length Normalized RDII Flow Rate (GPD/LF)	5.2

Hydrograph Conclusions:

- Clear markers of manhole F&C leakage but only during significant events
- Significant RDII with 1-2 day recovery period

Statistics Conclusions:


- Average GPD/EDU
- Moderate Baseline Infiltration
- Very Very High Peaking Factor (Even with Peaking factor suppressed because of high BI)
- High RDII/LF


SSES Recommendations:

- Nighttime weiring Priority 1
- Manhole frame and cover and clipped CO inspection/puddling investigation Priority 1



Hydrograph – RG10, 9/1/21 Storm





Modeling I&I Source Reductions



	Rehab Description	Inflow - Fast Dial	RII - Mediu m Dial	RII and BI - Slow Dial	BI - Very Slow Dial	Notes
1	Mainline lining without tap seals or end seals	0%	5%	5%	5%	Old school CIPP
2	Mainline lining with end seals but without tap seals Mainline lining with end	0%	10%	10%	10%	Mainline alone
3	seals and grouted tap seals	5%	20%	20%	20%	CIPPL + LTC stub
4	Mainline lining with end seals and tophat tap seals	5%	15%	15%	15%	CIPPL + Tophats
5	Mainline lining with end seals and full wrap tap seals	5%	25%	25%	25%	CIPPL + Stubby
6	Mainline lining with end seals and grouted tap and riser seals	10%	35%	40%	40%	CIPPL + LTC Shorti
7	LTC Grouting on mains already lined or grouted	10%	25%	30%	30%	LTC on previously lined/grouted main
8	Shorti Liner on mains already lined	10%	40%	40%	40%	Shorti on previously lined main
9	T Liner to property line cleanout on mains already lined	20%	45%	60%	60%	Tliner on previously lined main
1(LACO and LTC on previously lined/grouted main	20%	45%	60%	60%	
1	Mainline lining with end seals and full wrap tap and riser seals	10%	50%	50%	50%	CIPPL + Shorti
12	Mainline lining with end seals and T liner to property line cleanout	20%	55%	70%	70%	CIPPL + Tliner
	Mainline line with end seals, tap grouting, and LACO grouting	20%	55%	70%	70%	CIPPL + LTC + LACO
13		20%	55%	70%	70%	CIPPL + LTC + LACO


				RII and	BI -	
		Inflow - Fast	RII - Medium	BI - Slow	Very Slow	
	Rehab Description	Dial	Dial	Dial	Dial	Notes
14	Mainline lining with end seals and T liner to property line and 4x6 replacement	25%	65%	75%	75%	CIPP + Tliner through transition
15	Mainline lining with end seals and LACO to property line and 4x6 replacement	25%	65%	75%	75%	CIPP + LTC + LACO through Transition
16	Mainline grouting	0%	10%	10%	10%	MLJ
17	Mainline grouting with LTCs	10%	35%	40%	40%	MLJ and LTC
18	Mainline, LTC, and LACO grouting	20%	65%	65%	65%	MLJ, LTC, and LACO
19	Full Mainline Replacement - No manholes, no laterals	10%	50%	60%	60%	Replace main and riser
20	Full Mainline Replacement - includes manholes but no laterals	70%	70%	60%	60%	Replace main, manholes, and riser
21	Full Mainline Replacement - Manholes, laterals to curb	70%	75%	75%	75%	Replace main, manholes, and lateral to curb
22	Full Mainline Replacement - Manholes, laterals through transition	70%	75%	80%	80%	Replace main, manholes, and lateral to transition
23	Frame, Cover, and Chimney Sealing	50%	50%	10%	0%	F&C
24	Chimney sealing alone	10%	10%	10%	0%	Chimney
25	Manhole lining	5%	5%	5%	5%	FRCL
26	Manhole grouting	5%	5%	5%	5%	Injection Grout
27	Clipped Cleanout Sealing	10%	10%	5%	0%	Cap Clean out
28	Sump pump disconnect					Sump Disconnect
29	Roof Drain disconnect					Roof Drain disconnect
30	Storm/area drain disconnect					Area Drain disconnect

Next Steps




Common Sense I&I Reduction Blossom Impacts

- Late September
- Will show overflow locations/volumes without upsizing the system
- Will have an open system run to identify peak flow to KI WWTP if conveyance is upsized to eliminate impediments





What's not Removed must be Conveyed...... and Treated








Operating Guidelines

- Interceptor pressurization / hydraulic grade line limits
- Pump station operation rules
- Basement protection rules
- Interceptor Parallel vs. Enlargements
- Acceptable use of City interceptors

June 2022 – August 2022




Techniques for Fixing Problems





Preliminary Screening of Alternatives (PSOA)






- Revised/Finalized Source Reduction Plan(s)
- Revisions to operating guidelines
- Capital, O&M, Energy (carbon footprint), and Net Present Worth
- Design storm sensitivity
- Climate change considerations
- Sequence of construction

April 2023 – February 2024







Selection of Solution

- Short list of options
- Final proof of performance via 24year simulation
- Project sequence and schedule
- Bond and finance strategy
- Institutional approaches / intermunicipal agreements
- Decision-making
- Stakeholder involvement
- Approval & submission

March 2024 - June 2025







Discussion